

BIOSTAR

Matična ploča 1700 Biostar B760MXZ-E PRO DP/HDMI/DVI/VGA/M.2

Dostupnost: NA STANJU

MP cena: 16.490,00 din

Šifra proizvoda: B760MZ-E
PRO**14.390,00** din

Ušteda: 2.100,00 din

Opis

Čipset

Intel B760

Podrška za procesore

Podrška za 12th/13th Generaciju Intel Core™ i9/ i7/ i5/ i3 procesora i
Intel Pentium procesore/ Intel Celeron procesore u LGA1700 paketu

Memorija

Podrška Dual Channel DDR5 - 6000+(OC) / 6000(OC) / 5800(OC) /
5600(OC) / 5400(OC) / 5200(OC) / 5000(OC) / 4800
4 x DDR5 DIMM Memory Slot, Max. Supports up to 128 GB Memory
Each DIMM supports non-ECC 8/16/32GB DDR5 module
Support Intel® Extreme Memory Profile (XMP) memory modulesIntegrirana grafika (ako se stavi procesor koji ima
integriranu grafiku):Podrška DX12
Podrška HDCP

Skladištenje:	-2x M.2 socket and 4x SATA III (6Gb/s) ports -4 x SATA III Connector (6Gb/s) : Podržava AHCI, RAID 0, 1, 5, 10 & Intel Rapid Storage Technology -1 x M.2 (M Key) Socket (M2M_CPU): Podržava M.2 Type 2280 SSD module Podržava PCI-E 4.0 x4 (64Gb/s) - NVMe SSD 1 x M.2 (M Key) Socket (M2M_SB): Podržava M.2 Type 2242/2260/2280 SSD module Podržava PCI-E 4.0 x4 (64Gb/s) - NVMe SSD
LAN	Realtek RTL8125B 10/ 100/ 1000/ 2500 Mb/s auto negotiation, Half / Full duplex capability
Audio kodek	ALC897 7.1 Channels, High Definition Audio, Hi-Fi(Napred)
USB	1 x USB 3.2 (Gen2) Type-C port (1 preko internih priključaka) 5 x USB 3.2 (Gen1) port (3 nazad i 2 preko internih priključaka) 6 x USB 2.0 port (2 nazad i 4 preko internih priključaka)
Slotovi za proširenje	1 x PCIe 4.0 x16 Slot (x16 mode) 1 x PCIe 3.0 x16 Slot (x4 mode) 1 x PCIe 3.0 x1 Slot
Priključci pozadi:	2 x WIFI Antenna Port 1 x PS/2 Keyboard/ Mouse Port 1 x HDMI 1 x DP 1 x VGA 1 x DVI Port 3 x USB 3.2 (Gen1) Port 2 x USB 2.0 port 1 x LAN port 3 x Audio Jack
	4 x SATA III Connector (6Gb/s) 1 x M.2 (E Key) Socket : Podržava 2230 type Wi-Fi & Bluetooth module and Intel CNVi 2 x USB 2.0 Header (each header supports 2 USB 2.0 ports) 1 x USB 3.2 (Gen1) Header (each header supports 2 USB 3.2 (Gen1) ports) 1 x USB 3.2 (Gen2) Type-C Header (each header supports 1 USB 3.2 (Gen2) ports)

Interni priključci:	1 x 8-Pin Power Connector 1 x 24-Pin Power Connector 1 x CPU Fan Connector 1 x CPU water cooling connector (CPU_OPT) 1 x System Fan Connector 1 x Front Panel Header 1 x Front Audio Header 1 x Internal Stereo Speaker Header 1 x Clear CMOS Header 1 x COM Port Header 1 x TPM Header 2 x LED Header (5V) 1 x LED Header (12V)
H/W Monitoring (praćenje rada računara)	CPU / System Temperature Monitoring Smart / Manual CPU Fan Control CPU/DDR Voltage Monitoring
Dimenzije	Micro ATX Form Factor Dimenzije: 24.4 cm x 24.4cm (W x L)

Specifikacija