



ASRock

MB AM4 ASRock B550M-HDV 90-MXBDJ0-A0UAYZ

Dostupnost: NA STANJU

MP cena: 9.290,00 din

Šifra proizovda: 29869

8.190,00 din

Ušteda: 1.100,00 din

Specifikacija

- CPU
 - Supports AMD AM4 Socket Ryzen™ 3000, 3000 G-Series, 4000 G-Series, 5000 and 5000 G-Series Desktop Processors*
 - 6 Power Phase design
- *Not compatible with AMD Athlon™ Processors.
- Chipset
 - AMD B550
- Memory
 - Dual Channel DDR4 Memory Technology
 - 2 x DDR4 DIMM Slots
 - AMD Ryzen series CPUs (Vermeer) support DDR4 4600+(OC) / 4533(OC) / 4466(OC) / 4400(OC) / 4333(OC) / 4333(OC) / 4266(OC) / 4200(OC) / 4133(OC) / 4000(OC) / 3866(OC) / 3800(OC) / 3733(OC) / 3600(OC) / 3466(OC) / 3200 / 2933 / 2667 / 2400 / 2133 ECC & non-ECC, un-buffered memory*
 - AMD Ryzen series CPUs (Matisse) support DDR4 4600+(OC) / 4533(OC) / 4466(OC) / 4400(OC) / 4333(OC) / 4333(OC) / 4266(OC) / 4200(OC) / 4133(OC) / 4000(OC) / 3866(OC) / 3800(OC) / 3733(OC) / 3600(OC) / 3466(OC) / 3200 / 2933 / 2667 / 2400 / 2133 ECC & non-ECC, un-buffered memory*
 - AMD Ryzen series APUs (Cezanne) support DDR4 4733+(OC) / 4666(OC) / 4600(OC) / 4533(OC) / 4466(OC) / 4400(OC) / 4333(OC) / 4266(OC) / 4200(OC) / 4133(OC) / 4000(OC) / 3866(OC) / 3800(OC) / 3733(OC) / 3600(OC) / 3466(OC) / 3200 / 2933 / 2667 / 2400 / 2133 ECC & non-ECC, un-buffered memory*
 - AMD Ryzen series APUs (Renoir) support DDR4 4733+(OC) / 4666(OC) / 4600(OC) / 4533(OC) / 4466(OC) / 4400(OC) / 4333(OC) / 4266(OC) / 4200(OC) / 4133(OC) / 4000(OC) / 3866(OC) / 3800(OC) / 3733(OC) / 3600(OC) / 3466(OC) / 3200 / 2933 / 2667 / 2400 / 2133 ECC & non-ECC, un-buffered memory*
 - AMD Ryzen series APUs (Picasso) support DDR4 3533+(OC) / 3466(OC) / 3200(OC) / 2933 / 2667 / 2400 / 2133 non-ECC, un-buffered memory*
 - Max. capacity of system memory: 64GB**
 - Supports Extreme Memory Profile (XMP) memory modules
 - 15µ Gold Contact in DIMM Slots*

SR: Single rank DIMM, 1Rx4 or 1Rx8 on DIMM module label

DR: Dual rank DIMM, 2Rx4 or 2Rx8 on DIMM module label

**Due to the operating system limitation, the actual memory size may be less than 4GB for the reservation for system usage under Windows® 32-bit OS. For Windows® 64-bit OS with 64-bit CPU, there is no such limitation.

- BIOS
 - 256Mb AMI UEFI Legal BIOS with GUI support
 - Supports "Plug and Play"
 - ACPI 5.1 compliance wake up events
 - Supports jumperfree
 - SMBIOS 2.3 support
 - CPU, CPU VDDCR_SOC, DRAM, VDDP Voltage Multi-adjustment
- Graphics
 - Integrated AMD Radeon Vega Series Graphics in Ryzen Series APU*

- DirectX 12, Pixel Shader 5.0
- Shared memory default 2GB. Max Shared memory supports up to 16GB.**
- Three graphics output options: D-Sub, DVI-D and HDMI
- Supports Triple Monitor
- Supports HDMI 2.1 with max. resolution up to 4K x 2K (4096x2160) @ 60Hz
- Supports DVI-D with max. resolution up to 1920x1200 @ 60Hz
- Supports D-Sub with max. resolution up to 1920x1200 @ 60Hz
- Supports Auto Lip Sync, Deep Color (12bpc), xvYCC and HBR (High Bit Rate Audio) with HDMI 2.1 Port (Compliant HDMI monitor is required)
- Supports HDR (High Dynamic Range) with HDMI 2.1
- Supports HDCP 2.3 with DVI-D and HDMI 2.1 Ports***
- Supports 4K Ultra HD (UHD) playback with HDMI 2.1 Port
- Supports Microsoft® PlayReady

*Actual support may vary by CPU

**The Max shared memory 16GB requires 32GB system memory installed.

***Picasso supports HDCP 2.2 with HDMI 2.0 Port

- Audio
 - 7.1 CH HD Audio (Realtek ALC887/897 Audio Codec)
 - Supports Surge Protection
- LAN
 - PCIE x1 Gigabit LAN 10/100/1000 Mb/s
 - Realtek RTL8111H
 - Supports Wake-On-LAN
 - Supports Lightning/ESD Protection
 - Supports Energy Efficient Ethernet 802.3az
 - Supports PXE
- Slots
 - AMD Ryzen series CPUs (Vermeer and Matisse)**
 - 1 x PCI Express 4.0 x16 Slot (PCIe 1: x16 mode)*
 - AMD Ryzen series APUs (Cezanne and Renoir)**
 - 1 x PCI Express 3.0 x16 Slot (PCIe 1: x16 mode)*
 - AMD Ryzen series APUs (Picasso)**
 - 1 x PCI Express 3.0 x16 Slot (PCIe 1: x8 mode)*
 - 1 x PCI Express 3.0 x1 Slot

*Supports NVMe SSD as boot disks

- Storage
 - 4 x SATA3 6.0 Gb/s Connectors, support RAID (RAID 0, RAID 1 and RAID 10), NCQ, AHCI and Hot Plug
 - 1 x Hyper M.2 Socket, supports M Key type 2242/2260/2280 M.2 SATA3 6.0 Gb/s module and M.2 PCI Express module up to Gen4x4 (64 Gb/s) (with Vermeer, Matisse) or Gen3x4 (32 Gb/s) (with Cezanne, Renoir and Picasso)*

*Supports NVMe SSD as boot disks

Supports ASRock U.2 Kit

- Connector
 - 1 x SPI TPM Header
 - 1 x COM Port Header
 - 1 x Chassis Intrusion and Speaker Header
 - 1 x CPU Fan Connector (4-pin)*
 - 2 x Chassis Fan Connectors (4-pin) (Smart Fan Speed Control)**
 - 1 x 24 pin ATX Power Connector
 - 1 x 4 pin 12V Power Connector
 - 1 x Front Panel Audio Connector
 - 2 x USB 2.0 Headers (Support 4 USB 2.0 ports) (Supports ESD Protection)
 - 1 x USB 3.2 Gen1 Header (Supports 2 USB 3.2 Gen1 ports) (Supports ESD Protection)

*The CPU Fan Connector supports the CPU fan of maximum 1A (12W) fan power.

**The Chassis Fan supports the water cooler fan of maximum 1A (12W) fan power.
CHA_FAN2 can auto detect if 3-pin or 4-pin fan is in use.

- Rear Panel I/O
 - 1 x PS/2 Mouse/Keyboard Port

- 1 x D-Sub Port
- 1 x DVI-D Port
- 1 x HDMI Port
- 2 x USB 2.0 Ports (Supports ESD Protection)
- 4 x USB 3.2 Gen1 Ports (Supports ESD Protection)
- 1 x RJ-45 LAN Port with LED (ACT/LINK LED and SPEED LED)
- HD Audio Jacks: Line in / Front Speaker / Microphone

- Software and UEFI

Software

- ASRock Motherboard Utility (A-Tuning)
- ASRock XFast LAN

UEFI

- ASRock Full HD UEFI
- ASRock Instant Flash

*These utilities can be downloaded from ASRock Live Update & APP Shop.

- Support CD
 - Drivers, Utilities, AntiVirus Software (Trial Version), Google Chrome Browser and Toolbar
- Accessories
 - Quick Installation Guide, Support CD, I/O Shield
 - 2 x SATA Data Cables
 - 1 x Screw for M.2 Socket
- Hardware Monitor
 - Temperature Sensing: CPU, Chassis Fans
 - Fan Tachometer: CPU, Chassis Fans
 - Quiet Fan (Auto adjust chassis fan speed by CPU temperature): CPU, Chassis Fans
 - Fan Multi-Speed Control: CPU, Chassis Fans
 - CASE OPEN detection
 - Voltage monitoring: +12V, +5V, +3.3V, CPU Vcore
- Form Factor
 - Micro ATX Form Factor: 9.0-in x 7.9-in, 23.0 cm x 20.1 cm