



TP-LINK

SG3452X 48-port Gigabit Uprav.switch 4 10GE

Dostupnost: NA STANJU

MP cena: 85.290,00 din

Šifra proizvoda: LAN04218

77.790,00 din

Ušteda: 7.500,00 din

Specifikacija

Dodatne funkcije	
Dodatne funkcije	DHCP klijent, Statičko IP rutiranje, Port mirroring
Ostalo	Jumbo Frame do 9 KB, CE, FCC, RoHS sertifikovano, Mogućnost ugradnje u rack orman
Upravljanje	Web konfigurisanje, RMON, Web-bazirani interfejs (HTTP/HTTPS), System Log, Omada App, 1x MicroUSB tip B console port, Zero-Touch Provisioning, DHCP Auto Install, CLI (konzola, Telnet i SSH), GVRP
Fizičke karakteristike	
Boja	Crna
Dimenzije	440mm x 220mm x 44mm
Materijal	Metalno kućište
Pakovanje	Naponski kabl, Rack-mounting Kit, 1X QIG, gumene nožice
IPv6	
ACL	Da
Host	Da
MLD	v1 snooping, v2 snooping, Da
Statičke rute	Da
MAC adrese	
Filtriranje	Da
Ostalo	IP/MAC Binding, Maksimalno 64 pravila za filtere
Ručni unos	Da
Tabela	16k
Memorija	
Bafer	1.5MB
Mreža	
Forwarding	130.9Mpps
Protok	48x10/100/1000 Base-T, 1XConsole port, 4x10G SFP+, 1x Micro-USB Console Port
Protokoli	LACP, QoS, IGMP Snooping
Standardi	IEEE 802.3x, IEEE 802.1ab, IEEE 802.3u 100BASE-TX, IEEE 802.1d, IEEE 802.1w, IEEE 802.1p, IEEE 802.3ad, IEEE 802.1s, IEEE 802.1x, IEEE 802.1ax, IEEE 802.3ae, IEEE 802.3az EEE
Switchinga	176Gbps

	Osnovne karakteristike
Tip	Switch
Vrsta	Managed, Rackmount
	Ostalo
Upravljanje	Web konfigurisanje
	Priključci pozadi
Optički	4x SFP+
Ostali priključci	1x Console Port
RJ-45	48 (10/100/1000Mbps)
USB priključci	1 (Micro-B)
	Reklamacioni period
Reklamacioni period	24 meseca
	VLAN
Kapacitet	4k
Ostalo	Voice VLAN, VLAN tagging, VLAN Group
QinQ	Da
Standardi	IEEE 802.1q, 802.1ad
	Zaštita
Autentifikacije	802.1x, RADIUS, AAA, IP+MAC binding based on port, SSH, ACL, SSHv2, SSL, TLS, TACACS+, ARP detection, HTTPS
Monitoring	Filtriranje paketa, Ograničavanje portova, IEEE 802.1x kontrola protoka
Ostalo	Loop protection, CPU defense, IP source guard, User management, SNMP V1/V2/V3, AAA