

TP-LINK

SX3016F Omada L3 lite uprav,cloud switch 16porta



Dostupnost: NA STANJU

MP cena: 96.290,00 din

Šifra proizvoda: LAN04209

87.790,00 din

Ušteda: 8.500,00 din

Specifikacija

Dodatne funkcije	
Dodatne funkcije	Statičko IP rutiranje, Port mirroring, Dual Image, Dual Configuration, Cable Diagnostics, Reboot Schedule, Static Link Aggregation, Loop Prevention, Rate Limit, Batch Configuration, Batch Firmware Upg
Ostalo	Jumbo Frame do 9 KB, CE, FCC, RoHS sertifikovano, Physical Security Lock, 1x fan, LED indikator, 8 Priority Queues
Podržane tehnologije	IEEE802.3x Flow control
Upravljanje	RMON, SSH v2, Web (HTTPS), SNMP, System Log, Omada App, Zero-Touch Provisioning, DHCP Auto Install, CLI (konzola, Telnet i SSH), SNMP v3, SNTp, SDM Template, Cloud Access, MIBs, SNMP v2C, Centralized
Fizičke karakteristike	
Boja	Crna
Dimenzije	440mm × 220mm × 44mm
Materijal	Metalno kućište
Pakovanje	Naponski kabl, Rack-mounting Kit, 1X QIG, gumene nožice, 2 naponska kabla
IPv6	
ACL	Da
Host	Da
MLD	Da
Statičke rute	Da
MAC adrese	
Automatsko učenje	Da
Automatsko zastarivanje	Da
Filtriranje	Da
Ostalo	Maksimalno 64 pravila za filtere, IP/MAC Port Binding (512 Entries)
Ručni unos	Da
Tabela	32k
Memorija	
Bafer	24Mbit
Mreža	
Forwarding	238.01Mpps
Protok	10Gbps

Protokoli	IGMP Snooping, DLDP, MVR, MLD Snooping, PPPoE ID Insertion, ERPS, 802.3ah Ethernet Link OAM, sFlow
Standardi	IEEE 802.3x, IEEE 802.3ab, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1x, IEEE 802.1q, IEEE 802.3ah
Switching	320Gbps
Osnovne karakteristike	
Tip	Switch
Vrsta	Managed
Priključci pozadi	
Optički	16x 10G SFP+
Ostali priključci	1x RJ45 console port
USB priključci	1 x Micro USB
Reklamacioni period	
Reklamacioni period	24 meseca
VLAN	
Kapacitet	4k
Ostalo	Voice VLAN, VLAN Group, Protocol VLAN, MAC VLAN, GVRP, VLAN VPN, Private VLAN
QinQ	Da
Standardi	IEEE 802.1q
Zaštita	
Autentifikacije	802.1x, RADIUS, AAA, IP+MAC binding based on port, SSH, ACL, SSHv2, SSL, TACACS+, ARP detection, HTTPS, MAB, DoS Defend
Monitoring	Ograničavanje portova, IEEE 802.3x kontrola protoka
Ostalo	IP source guard, Guest VLAN, Storm Control, Port Isolation