



ASRock

MB s1700 ASRock H610M-H2/M.2 D4

Dostupnost: NA STANJU

MP cena: 7.890,00 din

Šifra proizvoda: 47450

6.990,00 din

Ušteda: 900,00 din

Specifikacija

- Unique Feature
Rock-Solid Durability
 - 3+1+1 Power Phase
- **EZ Update**
 - ASRock Auto Driver Installer
- CPU
 - Supports 14th, 13th & 12th Gen Intel® Core™ Processors (LGA1700)
 - Supports Intel® Hybrid Technology
 - Supports Intel® Turbo Boost Max 3.0 Technology
- Chipset
 - Intel® H610
- Memory
 - Dual Channel DDR4 Memory Technology
 - 2 x DDR4 DIMM Slots
 - Supports DDR4 non-ECC, un-buffered memory up to 3200
 - Supports ECC UDIMM memory modules (operate in non-ECC mode)
 - Max. capacity of system memory: 64GB
 - Supports Intel® Extreme Memory Profile (XMP) 2.0
- BIOS
 - 128Mb AMI UEFI Legal BIOS with GUI support
- Graphics
 - Intel® Xe Graphics Architecture (Gen 12)
 - 2 x HDMI 2.1 TMDS Compatible, support HDCP 2.3 and max. resolution up to 4K 60Hz
- * Intel® UHD Graphics Built-in Visuals and the VGA outputs can be supported only with processors which are GPU integrated.
- Audio
 - 7.1 CH HD Audio (Realtek ALC897 Audio Codec)
- LAN
 - Gigabit LAN 10/100/1000 Mb/s
 - Realtek 8111H
- Slots
 - CPU:
 - 1 x PCIe 4.0 x16 Slot (PCIe1), supports x16 mode*
 - Chipset:
 - 1 x PCIe 3.0 x1 Slot (PCIe2)*
- * Supports NVMe SSD as boot disks
- Storage
 - Chipset:
 - 1 x Ultra M.2 Socket (M2_1, Key M), supports type 2242/2260/2280 PCIe Gen3x4 (32 Gb/s) mode*
 - 4 x SATA3 6.0 Gb/s Connectors
- * Supports NVMe SSD as boot disks
- USB
 - 4 x USB 3.2 Gen1 Type-A (2 Rear, 2 Front)

- 6 x USB 2.0 (4 Rear, 2 Front)

* All USB ports support ESD Protection

- Connector
 - 1 x SPI TPM Header
 - 1 x Chassis Intrusion and Speaker Header
 - 1 x CPU Fan Connector (4-pin)*
 - 1 x Chassis/Water Pump Fan Connector (4-pin) (Smart Fan Speed Control)**
 - 1 x 24 pin ATX Power Connector
 - 1 x 8 pin 12V Power Connector
 - 1 x Front Panel Audio Connector
 - 1 x USB 2.0 Header (Supports 2 USB 2.0 ports)
 - 1 x USB 3.2 Gen1 Header (Supports 2 USB 3.2 Gen1 ports)

* CPU_FAN1 supports the fan power up to 1A (12W).

** CHA_FAN1/WP supports the fan power up to 2A (24W).

CHA_FAN1/WP can auto detect if 3-pin or 4-pin fan is in use.

- Rear Panel I/O
 - 1 x PS/2 Mouse/Keyboard Port
 - 2 x HDMI Ports
 - 2 x USB 3.2 Gen1 Type-A Ports
 - 4 x USB 2.0 Ports
 - 1 x RJ-45 LAN Port
 - HD Audio Jacks: Line in / Front Speaker / Microphone
- Software and UEFI
 - Software**
 - ASRock Motherboard Utility (A-Tuning)
 - UEFI**
 - ASRock EZ Mode
 - ASRock Full HD UEFI
 - ASRock My Favorites in UEFI
 - ASRock Auto Driver Installer
 - ASRock Instant Flash

*These utilities can be downloaded from ASRock Live Update & APP Shop.

- Accessories
 - 1 x I/O Shield
 - 2 x SATA Data Cables
 - 1 x Screw for M.2 Socket
- Form Factor
 - Micro ATX Form Factor: 8.66-in x 7.6-in, 22.0 cm x 19.3 cm
- OS
 - Microsoft Windows® 10 64-bit / 11 64-bit
- Certifications
 - FCC, CE
 - ErP/EuP ready (ErP/EuP ready power supply is required)

Link proizvođača: <https://www.asrock.com/MB/Intel/H610M-H2M.2/index.asp#Specification>